ELECTRIC PALLET TRUCK (JACK) (





 Entry roller Double fork roller



ELECTRIC PALLET TRUCK (JACK)

1 kg = 2.205 lh	1 inch = 25.4 mm

		g
Model		T-CBD15
Load capacity	Q (lbs)	3300
Load centre distance	C (inch)	23.6
Fork height (lowered)	h13 (inch)	3.1
Tyre size (front)	inch	Ø8.3 x 2.8
Tyre size (rear)	inch	Ø3.1 x3.7 / Ø3.1 x 2.8
Max. lift height	h3 (inch)	4.3
Height of tiller in drive position min./max.	h14 (inch)	25 / 47.2
Overall length	L1 (inch)	62.2 / 65
Length to face of forks	L2 (inch)	16.9
Overall width	b1 (inch)	21.6 / 27
Fork dimensions (S x E x L)	inch	2.1 x 6.3 x 45.3 (48)
Width overall forks	b5 (inch)	21.6 / 27
Aisle width for pallets 39.4" x 47.2" crossways	Ast (inch)	85.8 / 88.6
Aisle width for pallets 31.5" x 47.2" lengthways	Ast (inch)	80.7 / 82.1
Turning radus	Wa (inch)	54.3 / 57.1
Travel speed (laden / unladen)	mph	2.7 / 2.8
Battery voltage, nominal capacity K5	V/Ah	24 / 20
Battery weight	lbs	12.1
Service weight (with battery)	lbs	251.3

^{*} Option battery : 24V / 30Ah



Ruyi Handle




Emergency key switch




Entry roller



Horizontal motor Option : wheel protection plate





TAILIFT MATERIAL HANDLING TAIWAN CO., LTD.

No. 5, Zili 1st Road, Nankang Industrial Zone, Nantou city 540, TAIWAN Tel: +886-49-2263800 Fax: +886-49-2252919 Website: www.tailift.com E-mail: insales@tailift.com.tw

TAILIFT MATERIAL HANDLING USA,Inc.

5550 Jurupa St, Ontario, CA 91761 TEL: (909) 930–9801, (909) 930–9802

Website: www.tailift-usa.com

FAX: (909) 930-9739

DOC. S/N : DEB000 Edition : 01

